

Model: BMS - A208 (Li-ion 2S-2A)		
Test item (Test at normal temperature 25±2°C)		Criterion
Voltage	Charging voltage	DC: 8.4V CC/CV (4.2v/Cell) 1S
Supply Current	Normal operating mode current: Fuel gauge in NORMAL mode. ILOAD >Sleep Current	≤20uA
	Maximal continuous charging current	2A
	Maximal continuous discharging current	2A
	Balance current for single cell	/
Over-charge Protection (single cell)	Balance voltage for single cell	/
	Over charge detection voltage	4.25±0.025V
	Over charge detection delay time	0.5S—1.5S
	Over charge release voltage	4.05±0.05V
Over discharge protection (single cell)	Over discharge detection voltage	2.8±0.05V
	Over discharge detection delay time	50—150mS
	Over discharge release voltage	3.0±0.1V
Current protection (Battery pack)	ChargeOver current detection current	6±2A
	Detection delay time	5—15mS
	Discharge Over current detection current	6±2A
	Detection delay time	5mS—15ms
	Release condition	Cut load, Auto Recovery
Discharge Short protection	Detection condition	Exterior short circuit
	Detection delay time	200-500us
	Release condition	Cut load
Resistance	Main loop electrify resistance	≤50mΩ
Temperature	Operating Temperature Range	-20∼+60℃
	Storage Temperature Range	-20∼+65℃
SIZE: L49 *W6.5*T	2 mm	

NTC:/ Activation Method:/ Temperature switch: / Weak current switch: /

