

Model: BMS 1000 (Li-ion 10S15A) ver: A

| Test item (Test at normal temperature 25±2°C ) |  | Criterion                         |
|--|--|-----------------------------------|
| Voltage  | Charging voltage   | DC: 25.2V CC/CV<br>(4.2v/Cell) 6s |
| Supply Current                                 | Normal operating mode current: Fuel gauge in NORMAL mode. ILOAD >Sleep Current | ≤50uA                             |
|  | Maximal continuous charging current  | 5A                                |
|  | Maximal continuous discharging current   | 15A                               |
|  | Balance current for single cell  | 42±10mA                           |
| Over-charge Protection (single cell)           | Balance voltage for single cell  | 4.2V±0.05V                        |
|  | Over charge detection voltage  | 4.25±0.05V                        |
|  | Over charge detection delay time   | 0.5S—2S                           |
|  | Over charge release voltage  | 4.05±0.1V                         |
| Over discharge protection (single cell)        | Over discharge detection voltage   | 2.8±0.05V                         |
|  | Over discharge detection delay time  | 10—200mS                          |
|  | Over discharge release voltage   | 3.0±0.1V                          |
| Current protection (Battery pack)              | ChargeOver current detection current   | /                                 |
|  | Detection delay time   | /                                 |
|  | Discharge Over current detection current                                       | 50±10A                            |
|  | Detection delay time   | 5ms—50ms                          |
|  | Release condition  | Cut load,Auto Recovery            |
| Short protection                               | Detection condition  | Exterior short circuit            |
|  | Detection delay time   | 200-600us                         |
|  | Release condition  | Cut load                          |
| Resistance                                     | Main loop electrify resistance   | ≤ 60mΩ                            |
| Temperature                                    | high temperature discharge protection  | 70°C                              |
|  | Operating Temperature Range  | -40~+85°C                         |
|  | Storage Temperature Range  | -40~+125°C                        |

SIZE: L66 \*W49 \*T 10 mm

NTC: 10K NTC    Temperature switch: 70°C    Weak current switch: /    Activation Method:/

