

 PCM Specifications

Model: BMS -A1002(Li-ion 10S-15A)

Test item (Test at normal temperature 25±2℃)		Criterion
Voltage	Charging voltage	DC: 42V CC/CV (4.2v/Cell) 1S
Supply Current	Normal operating mode current: Fuel gauge in NORMAL mode. ILOAD >Sleep Current	≤50uA
	Maximal continuous charging current	8A
	Maximal continuous discharging current	15A
	Balance current for single cell	/
Over-charge Protection (single cell)	Balance voltage for single cell	/
	Over charge detection voltage	4.25±0.05V
	Over charge detection delay time	500-2000mS
	Over charge release voltage	4.15±0.05V
Over discharge protection (single cell)	Over discharge detection voltage	2.8±0.10V
	Over discharge detection delay time	500-2000mS
	Over discharge release voltage	3.0±0.10V
Current protection (Battery pack)	ChargeOver current detection current	12±3A
	Detection delay time	500-1500mS
	Discharge Over current detection current	50±10A
	Detection delay time	500-1500mS
	Release condition	Cut load/Charge
Discharge Short protection	Detection condition	Exterior short circuit
	Detection delay time	100-500us
	Release condition	Cut load/Charge
Resistance	Main loop electrify resistance	≤60mΩ
Temperature	Operating Temperature Range	-20~+70℃
	Storage Temperature Range	-40~+125℃

SIZE: L63*W34*T10mm±2

NTC:10K Temperature switch : / Weak current switch: / Activation Method:/

